

GIANT GUN SAFES

- Body & Door constructed from 12-gauge steel exterior
- Over 3/4 inch (.84) of steel between door and lock, including hardplate
- Body has a total of 2 pieces of 1/2 inch fire board for a total of 1 inch of fire board.
- Door has a total of 3 pieces of 1/2 inch fire board for a total of 1 1/2 inches of fire board.
- Door has fire-activated expanding door seal located on the door-frame on all four sides.
- Door bolts are 1 1/4 inches in diameter and are located on all 4 sides of the door.
- A total of 2 mounting holes sized 7/16 inch in diameter are located in the center of the safe's depth on the right and left sides.
- Dehumidifier access hole is 7/16 inch in diameter and located on the lower right hand corner of the back wall. Note that the fire board is not pre-drilled.
- The interior of the safe, the shelves, and the door back cover are all upholstered.
- Interior shelving are upholstered wood.
- Safe is U.L. listed as a RSC labelled safe.
- **1 Hour fire rating at 1200 degrees.**



RSC



16 Rifles

EV-5922

Outside H 59", W 22", D 16"
 Inside H 56.5", W 19.5", D 12.5"
 Weight 385 Lbs.

*(Add 2 3/4" for handle)



24 Rifles

EV-5930

Outside H 59", W 30", D 24"
 Inside H 56.5", W 27.25", D 20.25"
 Weight 605 Lbs.

*(Add 2 3/4" for handle & dial lock)



33 Rifles

EV-5939

Outside H 59", W 39", D 24"
 Inside H 56.5", W 36.5", D 20.25"
 Weight 740 Lbs.

*(Add 2 3/4" for handle & dial lock)



GIANT FB SERIES GUN SAFES

- Door: Fully fire proof insulated, 4 1/3" overall thickness including facial 1/4" steel plate, 1/8" middle steel plate, and 1/8" inner steel plate
- Body: 1/8" steel plate used for both inner and outer steel plates, plus 16 Gauge Reinforcement steel bracket added with 1-1/4" thick fire proof insulated construction
- Interior: Flexible design upholstered inside walls, shelving and door cover panel
- 1-1/4" dia chrome plated steel locking bolts
- 1-1/4" dia chrome plated dead bolts
- Glass relocking device
- Spring loaded auxiliary relocking
- 1/4" thick drill resistant harden plate (Ball bearing harden plate)
- Side punch attack resistant bolt work and 6 mm thick V shaped harden brackets
- Four recessed bolt down holes with plastic caps
- Expandable in-tumescent fire seal on 4 sides of door

15 Rifles

FBG-6022E

Outside H 59.3", W 22", D 20"
 Inside H 54", W 19.2", D 12.8"
 Weight 770 Lbs.
 Shelf 2



RSC



24 Rifles

FBG-6030E

Outside H 59.3", W 31.4", D 22.4"
 Inside H 54.5", W 26.9", D 16.5"
 Weight 995 Lbs.
 Shelf 4



RSC



32 Rifles

FBG-6036E

Outside H 59.3", W 36", D 26"
 Inside H 54.5", W 31.3", D 20.1"
 Weight 1187 Lbs.
 Shelf 4



RSC



35 Rifles

FBG-6636

Outside H 66", W 36", D 28"
 Inside H 61", W 33", D 20"
 Weight 1373 Lbs.
 Shelf 5



RSC



Not all Shelves shown in picture